



## Flow Sensor Amplifier SKZ

Amplifier for calorimetric flow sensors



- AC 230V, AC 115V
- DC 24V
- Relay-Output
- LED-display
- Temperature control
- Turn off delay



## Flow Sensor Amplifier SKZ

Amplifier for calorimetric flow sensors

Technical Data			
Ausführung	SKZ 400 WR	SKZ 400 WR-115	SKZ 400 GR
Dimensions			
Type	SKZ 400 WR	SKZ 400 WR-15	SKZ 400 GR
ID-No.	<b>P10501</b>	<b>P10502</b>	<b>P10503</b>
Output	 Relay	 Relay	 Relay
Supply voltage [V]	230 AC +10/-20%	115 AC +10/-15%	24 DC ±20%
Temperature [°C]	-20...+100 einstellbar		
Turn off delay [s]	0...25 adjustable		
Output	2x relay / change over		
Switching voltage [V]	250 AC / 60 DC		
Switching current [A]	4 AC / 4 DC		
Switching power max.	1000 VA / 60 W		
Ambient temperature [°C]	-20...+60		



## Flow Sensor Amplifier SKZ

Amplifier for calorimetric flow sensors

Technical Data			
Type	SKZ 400 WR	SKZ 400 WR-115	SKZ 400 GR
Protection [EN 60529]	terminal: IP 20 / housing: IP 40		
Connection	Terminal screws		